

Cisco WVC2300 Wireless-G Business Internet Video Camera with Two-Way Audio

Cisco Small Business Video Surveillance Cameras

High-Quality Wireless Video Surveillance Platform Provides Flexible Installation

Highlights

- Wireless box camera with interchangeable lenses and I/O ports that allow flexible installation for multiple applications
- High-quality CCD sensor with low-light sensitivity and an IR filter switcher provides optimal video image under a range of conditions
- Simultaneous dual codecs provide optimal combination of viewing and storage of video
- Two-way audio, IP multicast, 3GPP (3rd Generation Partnership Project), and lots of other advanced features make this solution ideal for surveillance deployments

Figure 1. Cisco WVC2300 Wireless-G Business Internet Video Camera with Two-Way Audio



Product Overview

Cisco® Small Business Video Surveillance products provide customizable ways for small business owners to monitor and protect their companies. These high-quality solutions can be optimized for many different applications and sites. Each camera can be quickly mounted using the bracket included in the package. Their compact form factor also enables the cameras to be put inside a protective enclosure for interior or exterior installations. The cameras use removable CS-mount lenses and can be customized with optional zoom, wide-angle, vari-focal, auto-iris, and other types of lenses as required for a specific application or setting.

The Cisco WVC2300 Wireless-G Business Internet Video Camera (Figure 1) can be mounted on any pan-tilt (PT) base that supports the Pelco D protocol and can be remotely rotated and controlled through an RS-485 interface. It has two input and two output ports, which can be used to connect the camera to an alarm panel, siren, passive infrared (PIR) sensors, smoke detectors, lighting switch (on/off), door sensors, etc.

The Cisco WVC2300 uses a high-quality progressive-scan charge-coupled device (CCD) sensor, delivering good-quality video. The CCD sensor also has low-light sensitivity so video can be captured even in environments with very low light or during near-dark times of day. Additionally, the camera incorporates an infrared (IR) cut filter that, when used with a separate IR lamp, allows for video capture in total darkness.

The Cisco WVC2300 camera supports dual codecs (MPEG-4 and MJPEG). Both codecs can be used simultaneously. MPEG-4 gives efficient bandwidth consumption with good-quality compression and is optimal for real-time viewing of video. MJPEG gives optimal video quality with lossy compression, making it ideal for large-volume storage to a network attached storage (NAS) device.

The Cisco WVC2300's audio capabilities include two-way audio, embedded microphone, external speaker and microphone ports, and voice compression. With extensive feature support, such as IP multicast, Real Time Streaming Protocol (RTSP), Real Time Protocol (RTP), and 3rd Generation Partnership Project (3GPP), it enables video to be viewed from multiple endpoints and client applications such as 3G phones, and QuickTime clients on PCs or Wi-Fi phones. The wireless capabilities of the WVC2300 include support for 1x2 multiple-input, multiple-output (MIMO), providing better range than traditional 802.11g, and strong wireless security utilizing Wi-Fi Protected Access (WPA). Support for multiple network protocols like 802.1p priority, 802.1Q VLANs, and Dynamic DNS (DDNS), make the solution ideal for multiple IP surveillance applications. The cameras can also be managed securely using HTTPS.

Features

- Standard box-type camera allows for flexible installation
- Mounts in a standard outdoor or indoor enclosure
- Provides controls for mounting on a Pelco pan/tilt base to control movement remotely
- Removable CS-mount lens enables the camera to be customized for multiple applications - including zoom lens, wide-angle, vari-focal, and auto-iris lenses
- 1/4-in. progressive-scan CCD sensor delivers good-quality video
- Low-light sensitivity with high-quality lens, sensor, and programmable IR cut filter capability
- Audio input/output for external microphone and/or speaker
- I/O ports facilitate alarm triggers, turn lights on and off, etc.
- IEEE 802.11b/g wireless support with 1x2 MIMO offers better wireless range and coverage
- Dual codecs (MPEG-4 and MJPEG) supported simultaneously
- IP multicast support
- RTSP video/audio streaming to unicast and multicast clients
- 4x digital zoom; can also use optical zoom with appropriate interchangeable lens
- 3GPP allows viewing of video on a mobile device

- Motion detection with event notifications to an email account or alarm log in the monitoring software
- JPEG snapshots at multiple resolutions that can be sent to an FTP server
- Overlay watermarks/graphics and text
- Up to 10 unicast users and unlimited multicast users
- Built-in web server for remote access over IP
- Secure control via HTTPS
- Includes software for monitoring and recording up to 16 cameras simultaneously

Specifications

Table 1 gives the specifications, package contents, and minimum requirements for the Cisco WVC2300 Wireless-G Business Internet Video Camera with Two-Way Audio.

Table 1. Specifications for the Cisco WVC2300 Wireless-G Business Internet Video Camera with Two-Way Audio

Specifications	
Standards	IEEE 802.11g, IEEE 802.11b, IEEE 802.3, IEEE 802.3u, IEEE 802.1p (quality of service [QoS] priority), IEEE802.1Q (VLAN), 802.11e (wireless QoS)
Protocols supported	TCP/IP, HTTP, Dynamic Host Configuration Protocol (DHCP), Simple Mail Transfer Protocol (SMTP), FTP, Network Time Protocol (NTP), DNS, Universal Plug and Play (UPnP), RTP, RTSP, and DDNS
Ports	Ethernet, microphone IN, speaker OUT, power (12V, 1A), general-purpose I/O (GPIO), 4-pin IRIS port
Buttons	Reset
Cabling type	Unshielded twisted pair (UTP) Category 5
LEDs	Power, Network
Camera type	Box
I/O ports	<ul style="list-style-type: none"> • RS-485 x 1 (2 pins) - supports Pelco D protocol commands • Input control x 2 (2 pins) • Output control x 2 (2 pins)
Lens	
Sensor	1/4-in. progressive CCD sensor
Illumination	0.4 LUX at f1.7
Lens type	CS-mount lens, fixed focus; adapter included for lenses that require more distance between sensor and lens
Focal length	500mm–infinity (for included lens)
Field of view	60° (for included lens)
Video resolution	640 x 480 (VGA), 320 x 240 (QVGA), 160 x 120 (QQVGA)
Frame rate	1 to 30 frames per second (selectable)
Iris	Provides iris control for CS-mount auto-iris lens when attached
Setup/Configuration	
Web user interface	Built-in web user interface for easy browser-based configuration (HTTP)
Management	
Web browser	<ul style="list-style-type: none"> • Internet Explorer 5.x or later • Limited support for Netscape and Firefox. Browser controls for pan/tilt/zoom (PTZ), audio, and motion detection are limited or not supported with Netscape and Firefox.
Event logging	Event logging (syslog)
Web firmware upgrade	Firmware upgradable through web browser

Video Compression	
Dual codec	<ul style="list-style-type: none"> • MPEG-4 simple profile • MJPEG • Simultaneous dual stream
Snapshot	JPEG
Modulation	National Television System Committee (NTSC) and Phase Alternating Line (PAL)
Image settings	Brightness and contrast
Zoom	4x digital zoom
Night vision	IR cut filter for low light
Video controls	Auto white balance (AWB), auto exposure (AES)
Image controls	Select video by quality, bandwidth, and frame rate
Format	3GPP for use with 3G phones
Alerts	
Motion detection	4 detection areas with individual sensitivity
Email alert	3 email addresses
FTP uploading	FTP server address and login settings
Instant messaging	Jabber client support
Scheduled	Schedule by day or time
Triggers	Input 1, Input 2, motion detection
Actions	Output 1, output 2, messaging, email, FTP
Audio	
Summary	<ul style="list-style-type: none"> • 2-way audio • Built-in microphone: 6 mm, -40 db + 3 db • Microphone input: 3.5-mm phone jack • Speaker output: 3.5-mm phone jack
Compression	G.726: 16 kbps, G.711 A-law and μ -law
Sampling rate	8 kHz
Default bit rate	16 kbps
Management Utility	
Monitoring/recording software	<ul style="list-style-type: none"> • Monitoring and recording for up to 16 cameras • Advanced search histogram or by time and date • Recording set up to record by motion trigger, manual, or schedule; recording and playback
Security	
Wired Equivalent Privacy (WEP)/WPA	WEP 64 bit/128 bit, WPA Temporal Key Integrity Protocol (WPA-TKIP), WPA Pre-Shared Key (WPA-PSK)
User list	User rights list to view video and/or to control camera functions
Username/password	Logon authentication: 20-character username and 8-character password
Kensington lock	Physical security option
Network	
RTP/RTSP	RTP and RTSP allow for viewing from any client supporting these protocols, like 3G phones or QuickTime client
NTP	Keeps time of camera in sync with your network
SMTP	Allows video clips to be emailed
FTP client	Facilitates scheduling transfer of images to an FTP server
DDNS	Facilitates reaching the camera by a name irrespective of the camera's IP address. Supports DDNS, TZO, and 3322 DDNS services
UPnP	Allows autodiscovery of the camera by other UPnP devices
IP filtering	Allow or disallow access by IP address

Power	
Power options	External power adapter: 12V 1A, 110~120V AC/60 Hz, switching
Power consumption	10W
Environmental	
Dimensions	4.72 x 2.99 x 1.81 in. (120 x 76 x 46 mm)
Unit weight	1.15 lb (0.52 kg)
Power	External power adapter 12V DC 1A 110~120V AC/60 Hz switching
Certification	FCC Part 15C Class B, CE, UL, EMC/EMI Part 15B Class B for US
Operating temperature	32° to 122°F (0° to 50°C)
Storage temperature	-4° to 158°F (-20° to 70°C)
Operating humidity	10% to 80%
Storage humidity	0% to 19%
Package Contents	
<ul style="list-style-type: none"> • Cisco WVC2300 Wireless-G Business Internet Video Camera • Stand kit • Antennas (2) • Power supply (12V 1A) • 6-foot Ethernet cable • CS-mount lens adapter ring for wider focal length lens • Allen wrench • Quick installation guide • Setup CD 	
Minimum Requirements	
<ul style="list-style-type: none"> • Wired Ethernet or wireless 802.11b/802.11g network • Network adapter with Ethernet network cable and TCP/IP installed per PC • Switch/router to support multiple connection points • Internet Explorer 5.x or later with ActiveX support for viewing • Microsoft Windows Vista, XP, 2000, ME, or 98SE • 2-GHz Pentium 4 or AMD Athlon-class CPU with 512 MB RAM • 128-MB AGP video adapter 	
Product Warranty	
3-year limited hardware warranty with return to factory replacement and 90-day limited software warranty.	

Cisco Limited Warranty for Cisco Small Business Series Products

This Cisco Small Business product comes with a 3-year limited hardware warranty with return to factory replacement and a 90-day limited software warranty. In addition, Cisco offers software application updates for bug fixes and telephone technical support at no charge for the first 12 months following the date of purchase. To download software updates, go to:

<http://www.cisco.com/go/smallbiz>.

Product warranty terms and other information applicable to Cisco products are available at

<http://www.cisco.com/go/warranty>.

For More Information

For more information on Cisco Small Business products and solutions, visit:

<http://www.cisco.com/smallbusiness>.



Americas Headquarters
Cisco Systems, Inc.
San Jose, CA

Asia Pacific Headquarters
Cisco Systems (USA) Pte. Ltd.
Singapore

Europe Headquarters
Cisco Systems International BV
Amsterdam, The Netherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at www.cisco.com/go/offices.

CCDE, CCENT, Cisco Eos, Cisco Lumin, Cisco Nexus, Cisco StadiumVision, Cisco TelePresence, Cisco WebEx, the Cisco logo, DCE, and Welcome to the Human Network are trademarks; Changing the Way We Work, Live, Play, and Learn and Cisco Store are service marks; and Access Registrar, Aironet, AsyncOS, Bringing the Meeting To You, Catalyst, CCDA, CCDP, CCIE, CCIP, CCNA, CCNP, CCSP, COVP, Cisco, the Cisco Certified Internetwork Expert logo, Cisco IOS, Cisco Press, Cisco Systems, Cisco Systems Capital, the Cisco Systems logo, Cisco Unity, Collaboration Without Limitation, EtherFast, EtherSwitch, Event Center, Fast Step, Follow Me Browsing, FormShare, GigaDrive, HomeLink, Internet Quotient, IOS, iPhone, iQuick Study, IronPort, the IronPort logo, LightStream, Linksys, MediaTone, MeetingPlace, MeetingPlace Chime Sound, MGX, Networkers, Networking Academy, Network Registrar, PCNow, PIX, PowerPanels, ProConnect, ScriptShare, SenderBase, SMARTnet, Spectrum Expert, StackWise, The Fastest Way to Increase Your Internet Quotient, TransPath, WebEx, and the WebEx logo are registered trademarks of Cisco Systems, Inc. and/or its affiliates in the United States and certain other countries.

All other trademarks mentioned in this document or website are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (0809R)